



FORESTRY, TIMBER AND ENVIRONMENT CONSULT SDN. BHD. (211109-U)

Level 8, Wisma General Lumber, Block D, Peremba Square,
Saujana Resort, 40150 Shah Alam, Malaysia.
Tel: +603 7847 1093 Fax: +603 7847 1095

EC - Declaration of conformity



The undersigned representing the following:

Manufacturer and the FORESTRY, TIMBER AND ENVIRONMENT Consult SDN. BHD	authorised representative established within the European Economic Area Sport Service Europe s.r.o.
Address of manufacturer Level 8, Wisma General Lumber, Block D, Peremba Square, Saujana Resor 40150 Shah Alam, Malaysia	Address of the authorised representative Šternberská 300 CZ-763 02 Zlín, Louky

herewith declare that the product: **Multi-layer parquet flooring**
Brands: TIMBER TOP, FLOOR ART, WOODLINE

are in conformity with the provisions of the following EC Directive 89/106/EHS, when installed in accordance with the installation
instructions and that the standard referenced below have been applied:

EN 14342: 2005 + EN 14342: 2005/AC: 2007 Wood flooring. Characteristics, evaluation of conformity and marking

Provisions to which the product conforms:

Characteristic	Performance declaration	Report
Reaction to fire	Class D _n - s1	ITT report No. Z-20/072/08/3501/SB 1)
Emission of formaldehyde	Class E1	Test report No. 277166 2)
Content of pentachlorophenol	≤ 5 ppm	Test report No. 277166 2)
Slipperiness	NPD	ITT report No. Z-20/072/08/3501/SB 1)
Biological durability	Use class 1	ITT report No. Z-20/072/08/3501/SB 1)

Description of the product and purpose and method of applying in building:

Wood multi-layer parquet (UTF Unique Timber Floors) is manufactured with dimensions (14,5 x 145/190 x 1820 mm) consists of a surface layer of single strip, two strips or three strips of the hardwood (species - oak, beech, ash, maple, walnut, merbau, kempas, jatoba, hevea and others with thickness (3,6 ±0,1) mm, middle layer of wood elements with thickness (9 ±0,1) mm and under layer veneer thickness (2 ±0,1) mm. The surface layer is finished with UV acrylic lacquer or UV oil from producer Klumpp, Germany. Floor panels are produced in tongue and groove version or in woodloc version (Välinge click).

Multi-layer parquets are delivered with commercial names: TIMBER TOP, FLOOR ART, WOODLINE

Product is designated for internal use as flooring in dry conditions with reaction to fire Class D_n-s1 for multilayer with surface coating and not specified above, minimum mean density 500 kg/m³, minimum overall thickness 14 mm with or without air gap underneath. In construction work are installed coated, varnished or oil-paint., in accordance with instruction of manufacturer (UTF Unique Timber Floors).

Name and address of testing laboratory:

- 1) LIGNOTESTING, a.s., Technická 5, SK-821 04 Bratislava, Slovakia
- 2) EPH Entwicklungs- und Prüflabor Holztechnologie GmbH, Zellescher Weg 24, D-01217 Dresden

Manufacturer and the Forestry, Timber & Environment Consult Sdn. Bhd.	authorised representative established within the European Economic Area
Signature: <i>Gurjeet Singh</i>	Signature: <i>Petr Král</i>
Name: GURJEET SINGH	Name: PETR KRÁL
Position: GROUP OPERATION DIRECTOR	Position: EXECUTIVE DIRECTOR
Date: 29/04/2008	Date: 06/05/2008



Sport Service Europe s.r.o.
Šternberská 300
763 02 ZLÍN, Louky
DIČ: CZ42340900